



LIGHTING SYSTEMS

Power Point



There are occasions where simple and reliable power distribution is required. The LSC PowerPoint is a simple-to-use and affordable power distribution unit

Download manual: <http://www.lslighting.com/products/power-distribution/powerpoint>

- Twelve 10A or 16A
- Individual RCD (30mA) protection for each output circuit – protection for users
- Individual circuit breaker for each output circuit
- Master isolator switch that disconnects Neutral from output circuits as well
- Three neon indicators show state of phase power
- Three-phase operation
- Single-phase operation possible

		PWP12/10	PWP12/16	PWP6/25
Output Circuits		12	12	6
Max Load per Circuit		10 Amps	16 Amps	25 Amps
Thermal / Magnetic Breakers		✓	✓	✓
RCD/GFI (RCBO) protection		✓	✓	✓
RCD/GFI (RCBO) Current Trip		30mA/Channel		
Master Isolator		80A 3phase switch	80A 3phase switch (PWP12/16A fitted with 32A 3phase MCB)	80A 3phase switch
Power Indicator for Each Phase		✓	✓	✓
Three Phase or Single Phase operation		✓	✓	✓
Output Connector Options (add subscript for connector type to model number above for full ordering code)	/A	12 x 3-pin Australian GPO style connectors	12 x 3-pin 20A Australian GPO style connectors	6 paired Australian GPO outlets (20A + 15A per chan-
	/P	12 x Powercon connectors		
	/S	12 x Shuko Connectors		N/A
	/T	Hardwired (terminals)		
	/W	2 x Wieland (Harting) 16-pin multi-		N/A
	/X	2 x 19-pin Socapex multi-pole connectors		1 x 19-pin Socapex multi-pole connector
Power Supply		Nominal 220-240 Volts. 3-phase star. 50-60Hz (Single phase operation possible - 63A max) Operating range typically 190-260V, 45-65Hz. 100-120 Volt models available on request		
Power Input Connection		All 10A models (and PWP12/16A) are fitted with a three phase 1.2m H07 5 core x 6.0mm ² rubber cable without plug. (Australian versions are supplied fitted with a 5 pin Clipsal plug as standard). All 16A models (excluding PWP12/16A) are supplied with a M25 metal cable gland and a 1.2m length of H07 5 core x 10.0mm ² rubber cable without plug. Hard-wired models are provided with 5 screw terminals for input power - no cable.		
Case		19" 3RU rackmount metal chassis		
Product Dimensions - W x D x H		483 x 300 x 132 mm		
Shipping Dimensions - W x D x H		580 x 500 x 210 mm		
Product Weight (Packed):		11 kg		10.5 kg